Environmental Protection Agency

BPT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per millior pounds) of lead pro duced from smelting	
Antimony	.367 .268 .054 .187 .000 5.248	.164 .110 .026 .078 .000 2.496

¹ Within the range of 7.5 to 10.0 at all times.

 $[49~\mathrm{FR}~8826,~\mathrm{Mar.}~8,~1984,~\mathrm{as}~\mathrm{amended}~\mathrm{at}~49~\mathrm{FR}~29795,~\mathrm{July}~24,~1984]$

§ 421.133 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable:

(a) Subpart M—Battery Cracking.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per milli pounds) of lead scr produced	
Antimony	1.299 .936 .189 .687	.579 .384 .087 .283

(b) Subpart M—Blast, Reverberatory, or Rotary Furnace Wet Air Pollution Control.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per millior pounds) of lead pro- duced from smelting	
Antimony	5.038 3.628 .731	2.245 1.488 .339

BAT EFFLUENT LIMITATIONS—Continued

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
ZincAmmonia (as N)	2.662 0.000	1.096 0.000

(c) Subpart M—Kettle Wet Air Pollution Control.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of lead produced from refining	
Antimony	.087	.039
Arsenic	.063	.026
Lead	.013	.006
Zinc	.046	.019
Ammonia (as N)	.000	.000

(d) Subpart M—Lead Paste Desulfurization.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pound pounds) o essed desulfurizat	f lead proc- through
Antimony	.000 .000 .000 .000	.000. 000. 000. 000.

(e) Subpart M—Casting Contact Cooling.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of lead cast	
Antimony	.042	.019
Arsenic	.031	.013
Lead	.006	.003
Zinc	.022	.009
Ammonia (as N)	.000	.000

(f) Subpart M-Truck Wash.

§421.134

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of lead pro duced from smelting	
Antimony Arsenic Lead Zinc Ammonia (as N)	.041 .029 .006 .021	.018 .012 .003 .009

(g) Subpart M—Facility Washdown.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of lead pro- duced from smelting	
Antimony	.000	.000
Arsenic	.000	.000
Lead	.000	.000
Zinc	.000	.000
Ammonia (as N)	.000	.000

(h) Subpart M—Battery Case Classification.

BAT EFFLUENT LIMITATIONS

Pollutant pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of lead scrap produced	
Antimony Arsenic Lead Zinc Ammonia (as N)	.000 .000 .000 .000	.000 .000 .000 .000

(i) Subpart M—Employee Handwash.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per millio pounds) of lead pro duced from smelting	
Antimony	.052 .038 .008 .028 .000	.023 .015 .004 .011

(j) Subpart M—Employee Respirator Wash.

40 CFR Ch. I (7-1-06 Edition)

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per millio pounds) of lead pro duced from smelting	
Antimony	.085	.038
Lead	.012	.006
Zinc	.045	.018
Ammonia (as N)	.000	.000

BAT EFFLUENT LIMITATIONS

(k) Subpart M—Laundering of Uniforms.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of lead pro- duced from smelting	
Antimony	.247 .178 .036 .131	.110 .073 .017 .054

§ 421.134 Standards of performance for new sources.

Any new source subject to this subpart shall achieve the following new source performance standards:

(a) Subpart M—Battery Cracking.

NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of lead scrap produced	
Antimony Arsenic Lead Zinc Zinc	1.299 .936 .189 .687	.579 .384 .087 .283
Ammonia (as N) Total suspended solids	.000	.000 8.076
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

(b) Subpart M—Blast, Reverberatory, or Rotary Furnace Wet Air Pollution Control.